HCA_VCA_XCA_ IO-AxxMIXW-3-BEM ED2.docx

Page 1 of 3

Created: 2020-02-11 Revised: 2020-02-11

Environmental Declaration Type II

GENERAL PRODUCT INFORMATION

Name of product(s) Packaging

HCA, VCA, XCA series covering all models from 151-3 up to 283DWM-4 and IO-AxxMIXW-3-BEM

Cardboard

COMPANY INFORMATION

Company, address and telephone

AB REGIN Box 116 SE-428 22 Kållered Sweden

Tel: +46 - (0)31 - 720 02 00 E-mail: info@regin.se

Company description

Regin is the collected trademark for products and systems in building automation. The company's knowledge is based on many years of wide experience in control, automation and flow control. AB Regin has a certified quality assurance system according to ISO 9001.

Ongoing environmental work

Regin designs products on commission from clients as well as for resale. Regin can control environmental aspects related to product development and when choosing suppliers and components.

PRODUCT INFORMATION

General

The recommended field of application is stated in the technical documentation.

There is an unambiguous and lasting label (manufacturer, product name, serial number etc) on the product.

The labelling is linked to the technical documentation which makes the product clearly identifiable.

Product design

The products consists of one or two assembled circuit boards and display depending on model. They are mounted in a plastic casing intended for DIN rail or be mounted in a cabinet.

The enclosure has two parts and is assembled without screws.

Component modules	Weight grams	Weight %
Enclosure	119-120	31-48
Electronics assembly	130-197	51-52
Display	71	0-18



HCA_VCA_XCA_ IO-AxxMIXW-3-BEM ED2.docx

Page 2 of 3

Created: 2020-02-11 Revised: 2020-02-11

PRODUCT INFORMATION, RESOURCES AND HAZARDOUS SUBSTANCES

Resources Hazardous

Component modules (metals, organic, non-organic substances substances) (Kd. Hg. Pb. PCB. F

bstances) (Kd, Hg, Pb, PCB, PVC, PBB, PBBE etc)

PCB assembly Epoxy, Cu, Fe, Ag, Sn TBBPA

Casing PC
Buttons Rubber
CR2032 battery Li

Notes, the product's content

PRODUCTION

The components are mounted manually and automatically and are thereafter soldered together with classified soldering. The environmental consequences are negligible and consist solely of air outlet from soldering.

The operation does not require licencing

DISTRIBUTION

Production origin Hultsfred, Sweden Mode of transportation Lorry, train

Mode of distribution The product is normally distributed via a warehouse/wholesaler

Wrapping Material Wood, paper, plastic

Packaging material can not be returned.

AB Regin is connected to FTI.

BUILDING PHASE

Documented instructions for mounting and commissioning are included with the product.

The instructions contain recommendations concerning

- Safeguard measurement for handling procedures and mounting.
- Handling of the product at the workplace and during mounting.

USAGE PHASE

Normal operation

The product requires energy (electricity) during normal operation. Power consumption is <2.5VA. The product does not have any environmental impact on the surrounding environment during normal operation.

Normally, the product does not require any maintenance.

It is possible to estimate the product's life span in advance.

There is no documentation concerning the expected life span when the product is under different conditions.

Documented instructions for appropriate operation and maintenance are supplied with the product.

Emergency

In case of fire the plastic may emit gases harmful to human health. The amounts of these substances are small compared with the size of the product.

Circuit boards may emit toxic flue gases.



HCA_VCA_XCA_ IO-AxxMIXW-3-BEM ED2.docx

Page 3 of 3

Created: 2020-02-11 Revised: 2020-02-11

DEMOLITION

The product is prepared for environmental-friendly dismantling.

Dismantling of the product:

- 1. Open the product cover according to the supplied instructions.
- 2. Use a screwdriver or other appropriate tool to separate the plastic, electronic parts and battery and recycle at appropriate facility.

WASTE MANAGEMENT

The long life span of the product means that the recycling situation may differ from today when the product is recycled.

The product is required, by law, to be handled according to standard waste management procedures. The materials can easily be separated to a high separation degree.

Plastic parts can, theoretically, be recycled. Recovering of energy through combustion is considered the best option in the present situation, since the plastic does not contain any substances dangerous to the environment.

Circuit boards with components are required by law to be dismantled and constituent components to be identified. Swedish companies in electronic recycling separate in three main fractions. Recycling of materials, recovering of energy and dangerous waste.

Identified metallic constituents are returned to metal recycling.

Combustible materials are returned for safe disposal in a licenced incinerator.

Dangerous waste is returned for destruction to a licenced entrepreneur.

